Via Italo Calvino 7 Lotto 1 - Edificio A13-14 20017 Rho (MI)

Tel +90 00 96560971 info@danetech.it www.danetech.it



Metrology Made Simple

Additel 959A **Hydraulic Ultra-high Pressure Test Pump**

- **Pressurize large-volume workload**
- Generate pressure to 40,000 psi (2,800 bar)
- Increase and decrease pressure smoothly
- Three pressure ports



OVERVIEW


The new Additel 959A Hydraulic Pressure Test Pump is a benchtop pressure pump designed to generate pressure to 40,000 psi (2,800 bar). This pump incorporates a dual-piston system which is ideal for filling large volume workload with the hand pump and providing smooth increase and decrease of pressure with the high pressure, fine adjust screw press. The 959A test pump incorporates an isolation valve which isolates the calibration volume from the check valve associated with the hand pump. Because the check valve can often be a source of leaks and maintenance, the isolation valve provides more stable measurements and reduces potential maintenance of the pump. The Additel 959A is an ideal comparison test pump for calibrating pressure measuring instruments such as test gauges, indicators or transducers.

FEATURES

- Generate Ultra-high Pressure Generate pressure up to 40,000 psi (2,800 bar)
- Hand pump to fill large volume systems
- Durable and Minimal Maintenance Isolation valve provides stable pressures while reducing maintenance on the hand pump check valve
- Easy-to-use 40,000 psi (2,800 bar) can be generated easily with the dual-piston system

ORDERING INFORMATION

Model Number



Pressure port type:

AF-Autoclave F-250-C female B2-1/2BSP female X-Customize M-M20X1.5 female

Accessories included

Diethylhexyl Sebacate: 1 bottle (250 ml) Carrying case (959-X-SET models only)

SPECIFICATIONS

- Media: Diethylhexyl Sebacate
- **Pressure Range**

0 to 40,000 psi (2,800 bar) gauge pressure.

Material

Ram/adapters: SS

Body: SS, aluminum, Copper

Seals: Buna-N, PTFE, Copper Alloy, Aluminum Alloy

- Reservoir capacity: 25.6 in³ (420 ml)
- Connection

Test Gauge Connection: Autoclave F-250-C, 9/16" -

18 UNF female

Reference Gauge Connection: Autoclave F-250-C,

9/16" - 18 UNF female

1/2BSP female and M20X1.5 female connections are available upon request

Dimensions: Height: 6.9" (175 mm)

Base: 17.9" (455 mm) x 15.0" (380 mm)

Weight: 28.7 lb (13 kg).

Volume Per Stroke: 0.227 in³ (3.72 ml)

Piston volume: Fine adjust piston: 0.152 in³ (2.5 ml)

Warranty: 1 year

Optional Accessories

Model number	Description
9201	Diethylhexyl Sebacate, 1 liter (1 quart)
ADT104	Adapters and fittings, 1/4HP male to various male and female connectors (17 pcs).
ADT959A-MK	Maintenance kit for Additel 959A pump
ADT100-959-HK	Hose Kit, External Reservoir Expansion Hose Kit for ADT959
9910	Carrying case for Additel 946A, Additel 959A or Additel 960