### Danetech srl Tel. +39 02 36569371 Lotto 1 - Edificio A13-14 info@danetech.it

# **Additel 992, 993**

## **Handheld Pneumatic Pressure Pump**







Dual-stage piston: Higher pressure with less effort

Multi-position versatility for on-site use

Lever pressurization: Efficient and quick stabilization

Portable: Weighs 3.5 lb (1.6 kg)

Low maintenance

#### **OVERVIEW**

The ADT992 and ADT993 Handheld Pneumatic Pressure Pumps offer a pressure range from 95% vacuum to 1,000 psi (70 bar), making them highly versatile for a wide range of applications. The ADT992 has a maximum pressure of 700 psi, while the ADT993 extends up to 1,000 psi. Designed for ease of use, the dual stage pre-pressure piston provides a broad pressure range and energy-efficient performance. The pump quickly stabilizes pressure with its lever-type pressurization system, and the fine adjustment screw ensures precise pressure settings. Its longitudinal layout enhances control during operation, and four different operating positions allow users to adapt to various work requirements, making it an ideal, modern replacement for traditional handheld pressure pumps.

#### **SPECIFICATIONS**

■ Media: Air

#### Generated Pressure Range:

ADT992: 95% vacuum to 700 psi (50 bar) ADT993: 95% vacuum to 1,000 psi (70 bar)

Adjustment Resolution: 10 Pa (0.1 mbar).

Minimum Pre-pressure: 600 psi (40 bar)

Boost pressure of lever stroke:

+30 psi (2 bar) / stroke Maximum load volume: 35 ml

Maximum volume of fine adjustment: 7.2 ml

#### **Multi-position Versatility**



**Horizontal Orientation** 

#### Port filters:

Standard port: 150µm quick removal filter Pump air intake port: 100µm quick removal filter Pressure outlet: 150µm quick release filter

Material:

Ram/adapters: SS Body: SS, aluminum

Seals: Buna-N, PTFE, Copper Alloy Dimensions: Height: 4.8" (122mm)

Base: 12.6" (320mm) x 4.3" (110mm)

Warranty: 1 year




Vertical Orientation



Tilt Head

#### ORDERING INFORMATION

#### Model Number



N -1/4NPT female N2 - 1/2NPT female

B - 1/4BSP female B2 - 1/2BSP female M-M20X1.5 female

SET: Pump and carrying case included

#### Accessories included

O-ring: 20 pcs

Flexible hose (Maximum pressure:630 bar) ADT100-X-FNG (adapter for DUT)

(X - designated by base model ordered)

Carrying case (992/993-X-SETmodels only)

#### Optional Accessories

- optional recognition				
Model number	Description			
ADT102	Adapters and fittings, 1/4NPT male to various male and female connection (25 pcs).			
ADT103	Adapters and fittings, 1/4NPT (1/2NPT, 1/4BSP, 1/2BSP, or M20X1.5) male to various female hand-tight quick connectors (10 pcs).			
9901-992	Carrying Case for one ADT992 or 993 hand pumps			
ADT992,993-MK	Maintenance kit for Additel 992,993 pump			
ADT100-X-FNG	Adapter for DUT connection (See below for configurations)			
NPTF4Q	NPTF2Q	BSPF4Q	BSPF2Q	M20FQ
1/4NPT female quick connector	1/2NPT female quick connector	1/4BSP female quick connector	1/2BSP female quick connector	M20X1.5 female quick connector
NPTF4	NPTF2	BSPF4	BSPF2	M20F
1/4NPT female	1/2NPT female	1/4BSP female	1/2BSP female	M20X1.5 female
NPTM4	NPTM2	BSPM4	BSPM2	M20M
	- 1			
1/4NPT Male	1/2NPT Male	1/4BSP Male	1/2BSP Male	M20X1.5 Male